

**SPECIFICATION DATA SHEET | MODEL : 05TCG**



The **TRANSCUBE™ 05TCG** is ideal for use in stand-by power applications and refueling for smaller equipment, such as industrial heaters, small generators, lighting towers... and more!

- ❖ **Transportable.** Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the tank full of fuel.
- ❖ **Stackable.** Easily stackable (2)-high full of fuel and (3)-high empty to reduce storage space requirements.
- ❖ **Accessible.** Access manway for maintenance and inspection of inner tank. Removable inner tank for servicing and cleaning.
- ❖ **Efficient.** Lockable equipment cabinet locks and secures equipment and fuel ports to run up to 3 pieces of diesel-powered equipment.
- ❖ **Environmentally Safe.** Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved.

**SPECIFICATIONS\***

STANDARD FITTINGS: High accuracy contents gauge; 3" Fill Point; 2" fusible link fill port; 1" pump feed with flexible dip pipe, strainer & non-return valve; (1) engine feed and return port set; pressure/vacuum vent; breather vent.  
 OPTIONAL FITTINGS: Complete transfer pump kits; water & particulate filter kits; fuel up to (2) feed & return blocks; fuel hose & quick couplers.

|   |  |
|---|--|
| <b>Capacity (Brim-Fill) Litres:</b> 500           | <b>Dimension Height (mm/in):</b> 836 mm/32.91"           |
| <b>Capacity (Brim-Fill) Imperial Gallons:</b> 110 | <b>Weight Empty (lbs/kg):</b> 880 lbs (399kg)            |
| <b>Capacity (Brim-Fill) US Gallons:</b> 132       | <b>Weight Full (lbs/kg):</b> 1995 lbs (905kg)            |
| <b>Dimension Length (mm/in):</b> 1153 mm/45.38"   | <b>Approvals:</b> UL142, ULC S-601-07, SUN IBC Type 31A, |
| <b>Dimension Width (mm/in):</b> 1152 mm/45.34"    | UN DOT, NFPA, Transport Canada, Vlare, Kiwa              |

\*Model specifications may slightly differ based on stock availability in your area. Please contact your local representative to confirm tank specifications.

