




## SPECIFICATION DATA SHEET | MODEL : 100TCG



The **TRANSCUBE™** Standby 100TCG is the solution to all your fuel delivery needs; On-site equipment refueling, direct back-up supply for diesel engines powering generators, compressors, pumps, HVAC.... and more!

-  **Accessible.** Access manway for maintenance and inspection of inner tank. Four-way forklift pockets for easy lifting when empty.
-  **Efficient.** Lockable equipment cabinet locks and secures equipment and fuel ports to run up to 2 pieces of diesel-powered equipment with a 3-point locking system and letterbox-style ports.
-  **Environmentally Safe.** Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved.

SPECIFICATIONS	
STANDARD FITTINGS: High accuracy contents gauge; 3" Fill Point; 2" fusible link fill port; 1" pump feed with flexible dip pipe, strainer & non-return valve; (1) engine feed and return port set; pressure/vacuum vent; breather vent. OPTIONAL FITTINGS: Complete transfer pump kits; water & particulate filter kits; additional set of feed & return blocks; fuel hose & quick couplers.	
<b>Capacity (Brim-Fill) Litres:</b> 8450	<b>Bund Material Thickness (in):</b> 1/8"
<b>Capacity (Brim-Fill) Imperial Gallons:</b> 1859	<b>Inner Tank Material Thickness (in):</b> 1/8"
<b>Capacity (Brim-Fill) US Gallons:</b> 2232	<b>Weight Empty (lbs/kg):</b> 7297 lbs (3310kg)
<b>Dimension Length (mm/in):</b> 2514 mm/99"	<b>Weight Full (lbs/kg):</b> 26035 lbs (11810kg)
<b>Dimension Width (mm/in):</b> 2261 mm/89"	<b>Approvals:</b> UL142, ULC S-601-07, NFPA
<b>Dimension Height (mm/in):</b> 2591 mm/102"	