










SPECIFICATION DATA SHEET | MODEL : TRANSTANK 100TT-DNV



The TransTank TT Series 100TT-DNV is a fully transportable, off-shore approved fuel container that is perfect for bulk transport and storage on off-shore sites.

-  Approved by Lloyd's Register to EN12079/DNV2.7-1 for safe off-shore use
-  Approved as a UN portable tank for transporting hazardous goods
-  Manhole for internal tank inspection, easy clean out and maintenance
-  Forklift pockets for easy handling
-  Sized for optimal logistic worldwide (10' container frame)
-  Double-walled, UL 142 design for environmental protection
-  Stackable 3 high full or 5 high empty
-  High quality marine grade paint on exterior of tank
-  Lockable equipment cabinet to secure all fittings and outlets within lockable secondary containment area

SPECIFICATIONS	
STANDARD FITTINGS: High accuracy contents gauge, 2" fill point with over fill prevention valve, 1" pump feed with flexible dip pipe, strainer & non-return valve, (1) engine feed and return port set, pressure/vacuum vent, breather vent. OPTIONAL: Painted interior (not to aviation fuel spec), Additional feeds and returns, Shackles, Lifting slings, Pumps and accessories.	
Capacity Litres: 8706	Weight Empty (lbs/kg): 9680 lbs (4390kg)
Capacity Imperial Gallons: 1915	SWL Weight (lbs/kg): 24200 lbs (10976 kg)
Capacity US Gallons: 2300	Max Rating (lbs/kg): 24200 lbs (10976 kg)
Dimension Length (mm/in): 2998 mm/118"	Approvals: UL142, USDOT, UN, ADR, RID, IMDG, UIC, TIR
Dimension Width (mm/in): 2438 mm/96"	CSC, PPG2/PPG26, EN12079/DNV2.7-1
Dimension Height (mm/in): 2438 mm/96"	