

## SPECIFICATION DATA SHEET I MODEL: TRANSTANK 100TT-IMDG





Whether your fueling needs are for bulk delivery, emergency supply, or military applications, the TRANSTANK TT Series is your quick & versatile fuel supply for generators, pumps & more!

- Transportable. Internal baffles prevent fuel surge and help stable handling and transportation at any fill level. Built to meet ISO container dimensions and can be transported full by Road, Rail or
- Stackable. Easily stackable (6)-high full of fuel, reducing transport and storage space requirements.
- Accessible. Access manway for maintenance and inspection of inner tank. Removable inner tank. for servicing and cleaning. Forklift pockets allow for easy handling of the tank full of fuel.
- Efficient. Our lockable equipment cabinet locks and secures equipment and fuel ports to run up to 4 pieces of diesel-powered equipment.
- Environmentally Safe. Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved.

## **SPECIFICATIONS**

STANDARD FITTINGS: High accuracy contents gauge; 3" fill point; 1" pump feed with flexible dip pipe, strainer & nonreturn valve; (1) engine feed and return port set; pressure/vacuum vent; breather vent, Access manway, Lockable Equipment Cabinet, overfill protection.

OPTIONAL: Complete transfer pump kits; inner tank coating; spill kits; fire extinguishers; water & particulate filter kits; up to (3) additional feed & returns; fuel hose & quick couplers, Hose reels, lighting kit, High level and low level sensor, portable generator, Oilfield Skid frame, Fuel recirculation polisher, Auxiliary hand pump, Fuel Sampling/Water drain off pump; Loading arms, Multiple fuelling points.

| Capacity (Brim-Fill) Litres: 7800           | Bund Material Thickness (in): 1/8"                    |
|---|---|
| Capacity (Brim-Fill) Imperial Gallons: 1716 | Inner Tank Material (in): 1/8"                        |
| Capacity (Brim-Fill) US Gallons: 2061       | Weight Empty (lbs/kg): 8157 lbs (3700kg)              |
| Dimension Length (mm/in): 2997.2 mm/118"    | Weight Full (lbs/kg): 24492 lbs (11110kg)             |
| Dimension Width (mm/in): 2438 mm/96"        | Approvals: UL142, USDOT, UN, ADR, RID, IMDG, UIC, TIR |
| Dimension Height (mm/in): 2438 mm/96"       | CSC, PPG2/PPG26                                       |



