

SPECIFICATION DATA SHEET | MODEL : 20TCG-OS



The TransCube 20TCG-OS is a double-walled fuel tank certified tank for Superior Environmental Compliance and Ease-of-Use. It is approved to Highest Standards for Safe Off-Shore use.

-  Approved by ABS to EN12079 for safe off-shore use.
-  Approved as a 31AY package for transporting hazardous goods in packing group II and III.
-  Manhole for internal tank inspection, easy clean out and maintenance.
-  Four-way forklift pockets for easy handling.
-  High quality marine grade paint on exterior of tank.
-  Stackable 3 high full or 5 high empty.
-  Double-walled, UL 142 design for environmental protection.
-  Lockable equipment cabinet to secure all fittings and outlets within lockable secondary containment area.

SPECIFICATIONS	
STANDARD FITTINGS: High accuracy contents gauge, 3" Fill point, 2" Fusible link fill port, 1" Pump feed with flexible dip pipe, strainer & non-return valve, (1) Engine feed and Return port set, Pressure/Vacuum vent, Breather vent, Statutory vent. OPTIONAL FITTINGS: Galvanized exterior, Painted interior (not to aviation fuel spec), Additional feeds and returns, Shackles, Lifting slings, Pumps and accessories.	
Capacity Litres: 1970	Tare Weight (T): 2292 lbs (1040kg)
Capacity Imperial Gallons: 434	Payload (P): 4409 lbs (2000kg)
Capacity US Gallons: 520	Gross Weight (R): 6701 lbs (3040kg)
Dimension Length (mm/in): 2210 mm/87"	Approvals: ABS to EN12079, UL142, ULC S-601-07,
Dimension Width (mm/in): 1400 mm/55"	SUN IBC Type 31A, UN DOT, NFPA, Transport Canada,
Dimension Height (mm/in): 1296 mm/51"	Vlarem, Kiwa
Design Temperature (°C): -40°C	