









**SPECIFICATION DATA SHEET | MODEL : 30TCG-OS**



The TransCube 30TCG-OS is a double-walled fuel tank certified tank for Superior Environmental Compliance and Ease-of-Use. It is approved to Highest Standards for Safe Off-Shore use.

-  Approved by ABS to EN12079 for safe off-shore use.
-  Approved as a 31AY package for transporting hazardous goods in packing group II and III.
-  Manhole for internal tank inspection, easy clean out and maintenance.
-  Four-way forklift pockets for easy handling.
-  High quality marine grade paint on exterior of tank.
-  Stackable 3 high full or 5 high empty.
-  Double-walled, UL 142 design for environmental protection.
-  Lockable equipment cabinet to secure all fittings and outlets within lockable secondary containment area.

SPECIFICATIONS	
STANDARD FITTINGS: High accuracy contents gauge, 3" Fill point, 2" Fusible link fill port, 1" Pump feed with flexible dip pipe, strainer & non-return valve, (1) Engine feed and Return port set, Pressure/Vacuum vent, Breather vent, Statutory vent. OPTIONAL FITTINGS: Galvanized exterior, Painted interior (not to aviation fuel spec), Additional feeds and returns, Shackles, Lifting slings, Pumps and accessories.	
<b>Capacity Litres:</b> 3000	<b>Tare Weight (T):</b> 3658 lbs (1660kg)
<b>Capacity Imperial Gallons:</b> 661	<b>Payload (P):</b> 6614 lbs (3000kg)
<b>Capacity US Gallons:</b> 793	<b>Gross Weight (R):</b> 10273 lbs (4660kg)
<b>Dimension Length (mm/in):</b> 2210 mm/87"	<b>Approvals:</b> ABS to EN12079, UL142, ULC S-601-07,
<b>Dimension Width (mm/in):</b> 1981 mm/78"	SUN IBC Type 31A, UN DOT, NFPA, Transport Canada,
<b>Dimension Height (mm/in):</b> 1296 mm/51"	Vlarem, Kiwa
<b>Design Temperature (°C):</b> -40°C	