









**SPECIFICATION DATA SHEET I MODEL : TRANSTANK P75-NPB**



-  Self bunded or double wall design
-  Overfill protection supplied with mechanical shutoff and audible / visual alarm
-  Free to air vent with weather cap
-  Calibrated fluid level dipstick
-  Antisiphon valve installed
-  Tank floor has fall to front for water collection
-  Statutory signage
-  Under tank visibility

SPECIFICATIONS	
STANDARD FITTINGS: container corner castings, regulatory access manway, water evacuation pipe, interstitial space fluid dipstick, containment compartment with pressure vent, marine grade polyurethane paint (white in color)	
OPTIONAL: lockable pump bay with ladder	
<b>Capacity (Brim-Fill) Litres:</b> 72450	<b>Dimension Height (mm/in):</b> 2896 mm/114"
<b>Capacity (Brim-Fill) Imperial Gallons:</b> 15936	<b>Weight Bare Tank (lbs/kg):</b> 24692 lbs (11200kg)
<b>Capacity (Brim-Fill) US Gallons:</b> 19139	<b>Approvals:</b> UL142, ULCS601, AS1940, AS1692
<b>Dimension Length (mm/in):</b> 12191 mm/480"	
<b>Dimension Width (mm/in):</b> 2438 mm/96"	